



**K200**

## ➔ Proximity Time and Attendance System

Card Capacity : 30,000  
 Transaction Storage : 50,000  
 Card Reader : NA  
 Card Storage : NA  
 CPU : 32 bit microprocessor  
 Read Range : 8-10 cms  
 FAR :  $\leq 0.0001\%$  / FRR :  $\leq 1\%$   
 Identification Speed :  $\leq 0.5$  sec  
 Algorithm Ver : 10  
 Display : 128 x 64 OIED with white Color  
 Keypad : 4 x 4 Keypad  
 LED Indicator : Green/Red  
 Schedule Bell/Speaker : Mini Speaker  
 Push data : NA  
 Communication : RS232/485, TCP/IP  
 Camera : High Resolution Infrared Camera  
 Standard Features : DLST  
 Power Supply : 5V DC, 400mA  
 Operating Temperature : 0°C to 45°C  
 Operating Humidity : 20% -80%  
 Dimension : 90 x 190 x 3.5 mm

### Access Control:

Wiegand: NO  
 Relay: NO  
 Support Fire Alarm: NA  
 Door Sensor: NA  
 Anti passback: NA  
 Door Bell: NA

### Compatibility :

- External Speaker output available (Optional)
- External Bulb output available (Optional)
- 3rd party electric lock, Door sensor, Exit button

### Compatible Software & SDK :

- Smart office suite desktop
- Etime track lite desktop & web
- SDK for desktop applications
- Web based Device Manager/ePush server using Push data. Helps developers & integrators
- Supports 3rd Party Payroll/HRMS/ERP & Other applications