



Multibio 800

➔ Multi-biometric Time Attendance and Access Control System

Face capacity : 400(1:N)
Fingerprints templates : 1000
Card Storage : 10,000(Optional)
Transaction storage : 1,00,000
Card reader : ID
CPU : 800 Mhz 32 bit Microprocessor
Fingerprint sensor : 500 DPI Optical sensor
FAR : $\leq 0.0001\%$
FRR : $\leq 1\%$
Identification speed : < 0.5 sec
Algorithm Ver : 10
Display : 2.8 inch TFT LCD Color Screen
Keypad : 4 x 4 with 5 function Keys
LED Indicator : Green/Red
Schedule Bell/Speaker : Mini Speaker
Communication : TCP/IP, RS232/485, USB Host
Push data : Optional
Power Supply : 12V DC, 3A
Operating Temperature : 0 °C - 45 °C
Operating Humidity : 20% - 80%
Wiegand : IN / OUT
Relay : 12 V relay for lock EM lock, Bolt Lock or Strike lock

Support Fire Alarm : Yes
Door Sensor : Yes
Anti Passback : Yes
Door Bell : Yes
Support exit readers : No
Battery : Yes

Compatible :

- Compatible with Multi Door controllers via weigand
- External Speaker output available (Optional)
- External Bulb output available (Optional)

Compatible Software and SDK:

- Smart Office Suite Desktop
- Etime Tracklite Desktop
- SDK for desktop applications
- Web based Device Manager/ePush server using Push data. Helps developers & integrators
- Supports 3rd Party Payroll/HRMS/ERP and Other applications