



Iclock 990

➔ Standalone TFT - Fingerprint Time Attendance & Access Control System

Fingerprint Templates : 10,000
Card Capacity : 10,000
Transaction Storage : 2,00,000
Card Reader : Yes
CPU : 32 bit Microprocessor
Fingerprint Sensor : 500 DPI Optical sensor
(Optional Secugen STQC certified sensor)
FAR : $\leq 0.0001\%$ / FRR : $\leq 1\%$
Identification Speed : < 1 sec
Algorithm Ver : 10
Display : 3.5" Color TFT
Keypad : 4 x 4 with 5 function Keys
Schedule Bell/Speaker : Mini Speaker
Communication : TCP/IP, USB,
(Optional : Wifi, GPRS, GPRS)
Push data : Inbuilt
Standard Features : work code, SMS, DLST,
Self service query, Status Switch
Power Supply : DC 12V: 3Amp
Operating Temperature : 0°C to 45°C
Operating Humidity : 20% -80%
Dimension : 210 x 157 x 40mm

Access Control : Wiegand : In & Out
both 26 or 34 bit (With or without site code)
Relay : 12 V relay for lock EM lock,
Bolt Lock or Strike lock
Support Fire Alarm : Yes / Door Sensor ; Yes
Anti Passback : Yes / Door Bell : Yes
Support exit reader : 101 HE , FR 1200, Push Button
Battery : Yes / Card Readers : Yes
Communication : Wifi/GPRS
Sensor : Mifare/HID Prox/HID Iclass

Compatibility :

- Compatible with Multi Door controllers via weigand
- External Speaker output available (Optional)
- External Bulb output available (Optional)
- Support External Printer

Compatible Software & SDK :

- Smart office suite desktop and web
- Etime track lite desktop & web
- SDK for desktop applications
- Web based Device Manager/ePush server using Push data. Helps developers & integrators
- Supports 3rd Party Payroll/HRMS/ERP and Other applications